Model Number

KLR-C10-1,25-2,0-K144

Plastic fiber optic - diffuse

Features

- Coaxial
- Side light outlet enables installation when space is at a premium

Series

Fiber optic amplifiers

Device series	SU18 ; SU18/35 ; SU19

Description

Attention:
Fiber optics must not be twisted or kinked. Excessive tensile loads will lead to destruction. Contact with petrol or organic solvents must be prevented.

Accessories

OMH-LL-M3
Mounting bracket for fiber optic cable, M3 thread

Technical data

General specifications		
Sensor range		SU18: 30 mm SU18/35: 95 mm SU19: 30 mm
Fiber optic length	l	2000 mm , adjustable
Fiber optic diameter	d	1.25 mm
Adapter form		00
End piece		Thread / cylindrical right angle
Bending radius		min. 15 mm
Fiber configuration	Fv	see dimensions
Angle of divergence		67 °
Accessories provided		Cutter for plastic fiber optics
Ambient conditions		
Ambient temperature		-55 ... 70 °C (-67 ... 158 °F)
Mechanical specifications		
Material		
Optical face		plastic
Sheathing		PVC
Core		plastic
End piece		Stainless steel 1.4305 / AISI 303

Dimensions



Release date: 2014-07-09 15:56 Date of issue: 2014-07-09 807319_eng.xml