CERTIFICATE OF COMPLIANCE

Certificate Number E231213

Report Reference E231213-2019-09-04

Date 2022-July-25

Issued to: Pepperl+Fuchs SE

Lilienthalstrasse 200 Mannheim 68307 DE

This is to certify that representative samples of

CABLE ASSEMBLIES AND FITTINGS FOR INDUSTRIAL

CONTROL AND SIGNAL DISTRIBUTION

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 2238, Cable Assemblies and Fittings for Industrial

Control and Signal Distribution,

CSA C22.2 NO. 182.3-16 Special Use Attachment Plugs,

Receptacles And Connectors.

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





CERTIFICATE OF COMPLIANCE

Certificate Number E231213

Report Reference E231213-2019-09-04

Date 2022-July-25


This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Product Designation(s):

Cable Assemblies Cat. Nos. V1, V11, V15, V3, V31 or V311 may be followed by S, may be followed by B or D, followed by G or W may be followed by M, R or X, may be followed by V2A or V4A, may be followed by A2, E0, E2, E2/E3, E8, E8W, E10, E10W, may be followed by one or two characters, may be followed by two characters, followed by the cable length in meter + M, followed by PVC, PUR or POC, may be followed by one or more item from U, O, R or A with – or /, may be followed by an additional digit, may be followed by one, two or three characters, may be followed by V1, V11, V15, V3, V31 or V311, may be followed by S, may be followed by B or D followed by G or W may be followed by M, R or X, may be followed by V2A or V4A, may be followed by A2, E0, E2, E2/E3, E8, E8W, E10, E10W, may be followed by additional characters.

Male and female cable fitting Cat. Nos. V1, V11, V15, V3, V31 or V311 may be followed by S, may be followed by B or D, followed by G or W may be followed by M, R or X, may be followed by V2A or V4A, may be followed by A2, E0, E2, E2/E3, E8, E8W, E10, E10W, may be followed by one or two characters, may be followed by two characters, followed by the cable length in meter + M, followed by PVC, PUR or POC, may be followed by one or more item from U, O, R or A with – or /, may be followed by an additional digit.

Splitters cordset, Cat. No. V1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D, followed by G or W may be followed by M, R or X, may be followed by V2A or V4A, may be followed by "/" and then V1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D, followed by G or W, may be followed by M, R or X, may be followed by V2A or V4A followed by –A2, E0, E2, E2/E3, E8, E8W, E10, E10W or blank, followed by the cable length in meter + M, may be followed by "/" and then by the cable length in meter + M, followed by PVC, PUR or POC, followed by –YZZZ or –TZZZ, where ZZZ can be any character including blank denoting the interconnection within the splitter or denote –YEE or -TEE, -Y2 or -T2 or -Y24B or -T24B, may be followed by —TQ, may be followed by one or more item from U, UL, O, R or A with – or /, may be followed by an additional digit, may be followed by one, two or three characters, may be followed by V1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D followed by G or W may be followed by M, R or X, may be followed by V2A or V4A may be followed by one to four characters, may be followed by additional characters.





CERTIFICATE OF COMPLIANCE


Certificate Number E231213


Report Reference E231213-2019-09-04

Date 2022-July-25

Stand-alone splitters, Cat. No. V1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D, followed by –YZZZ or –TZZZ, where ZZZ can be any character including blank denoting the interconnection within the splitter or denote –YEE or -TEE, -Y2 or -T2 or -Y24B or -T24B, may be followed by –TQ, followed by V1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D, may be followed by W1, V11, V15, V3 or V31, may be followed by S, may be followed by B or D, may be followed by additional characters.

Male-to-Male configurations with the limitation of Class 2 circuits (having voltage rating of 30 V ac / 42 V dc or less) are covered. Other Male-to-Male configurations are not covered due to accessibility of live parts.





UL LLC

