Certificate Number UL-US-2123898-2 Report Reference E87056-20160315

Date 9-Sep-2022

Issued to: Pepperl+Fuchs SE

Lilienthalstrasse 200 Mannheim 68307

Germany

This is to certify that NRKH - Proximity Switches representative samples of Soc Addondum Page for Pr

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision

Date: 2019-05-06, UL 60947-5-2, 3rd Ed., Issue Date:

2014-03-28

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.






**Certificate Number** UL-US-2123898-2 **Report Reference** E87056-20160315 **Date** 

9-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
Cat. No. N followed by B or E,, followed by B or N, followed by numeric characters, followed by U1, U2, -U3, -U3PE, -U4, -U4PE may be followed by L, may be followed by K, followed by -UU, -U0 or -US, may be followed by -C, -C3 or -T, may be followed by -V93, may be followed by -Y may be followed by letters and/or numbers up to eight digits.	Proximity switches, AC/DC
Cat. No. N followed by B, E, R or S,, followed by B or N, followed by numeric characters, followed by U1, -U2, -U3, -U4, -U10, L2 or L3 may be followed by L may be followed by K may be followed by M, followed by -E0, -E1, -E2, -E3, -E34, -EP, -2E2, -A0, -A2, -Z0, -Z1, -Z2, -I, -U, -N0, -N1, -SN, -S1N, -B3 or -B3B may be followed by -IO may be followed by -C, C3 or -T, may be followed by -xM or -xMM, may be followed by -V1 or -V93, may be followed by -3G-3D, -M1, -M or -S2D2, or may be followed by -Y may be followed by letters and/or numbers up to eight digits	Proximity switches, Class 2 or LVLC





Certificate Number UL-CA-2119599-2
Report Reference E87056-20160315

Date 9-Sep-2022

Issued to: Pepperl+Fuchs SE

Lilienthalstrasse 200 Mannheim 68307

Germany

This is to certify that representative samples of

NRKH7 - Proximity Switches Certified for Canada See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 60947-5-2-14, 1st Ed., Issue Date: 2014-

03-28, CSA C22.2 NO. 60947-1-13, 2nd Ed., Issue Date:

2013-07-31

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.





**Certificate Number** UL-CA-2119599-2 **Report Reference** E87056-20160315 **Date** 

9-Sep-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

М	Model	Category Description
	Cat. No. N followed by B or E,, followed by B or N,	Proximity switches, AC/DC
fo	bllowed by numeric characters, followed by U1, U2, -U3,	Jr:36Ur:36Ur:36Ur:36Ur:36
	-U3PE, -U4, –U4PE may be followed by L, may be followed by K, followed by -UU, -U0 or -US, may be	
	followed by -C, -C3 or -T, may be followed by -V93,	
r	may be followed by -Y may be followed by letters and/or	L-Maryani-Maryani-Ma
	numbers up to eight digits.	リベンス・アイン
(	Cat. No. N followed by B, E, R or S,, followed by B or N,	Proximity switches, Class 2 or LVLC
	followed by numeric characters, followed by U1, -U2, -	I. MILAMILAMILAMI
	U3, -U4, –U10, L2 or L3 may be followed by L may be	
	followed by K may be followed by M, followed by –E0, -	$\times \times \times \times \times$
	E1, -E2, -E3, -E34, -EP, -2E2, -A0, -A2, -Z0, -Z1, -Z2, -I,	r. Vm. Vm. Vm. Vm. Vi
	U, -N0, -N1, -SN, -S1N, -B3 or -B3B may be followed by –IO may be followed by –C, C3 or –T, may be followed	リースト ビレスト ビレスト ビレスト
	by -xM or -xMM, may be followed by -V1 or -V93, may	
	be followed by -3G-3D, -M1, -M or -S2D2, or may be	
	followed by -Y may be followed by letters and/or	J_)(:U_)(:U_)(:U_)(:U_)(:U_)(:U_)(:U_)(:U
	numbers up to eight digits	

