

CERTIFICATE OF COMPLIANCE

Certificate Number 20170623-E87056
Report Reference E87056-20170623
Issue Date 2017-JUNE-23

Issued to: Pepperl+Fuchs GMBH
LILIENTHALSTRASSE 200
68307 MANNHEIM GERMANY

**This is to certify that
representative samples of** PROXIMITY SWITCHES
SEE ADDENDUM PAGE

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1, CSA C22.2 No. 60947-1, Low-Voltage
Switchgear and Controlgear - Part 1: General Rules.
UL 60947-5-2, CSA C22.2 No. 60947-5-2, Low-voltage
switchgear and Controlgear - Part 5-2: Control circuit
devices and switching elements - Proximity switches.

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20170623-E87056
Report Reference E87056-20170623
Issue Date 2017-JUNE-23

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Enclosed inductive proximity switches F25 family,
Cat. Nos. N, followed by B or C, followed by N, followed by 4, followed by -F25, followed by -E8, -2E2 or -2Z4L, may be followed by -FE, -M, -M1, -NE/FE, -NFE or -P, may be followed by -, may be followed by up to three digits and MM or M, may be followed by -PVC, may be followed by -V1, may be followed by -Y and any combination of letters and/or numbers.

Enclosed inductive proximity switches F25K family,
Cat. Nos. N, followed by B or C, followed by N, followed by 4, followed by -F25K, followed by -E8, -2E2 or -2Z4L, may be followed by -FE, -M, -M1, -NE/FE, -NFE or -P, may be followed by -S or -K, may be followed by -V1, may be followed by -Y and any combination of letters and numbers.

Accessory, Activator, Cat. No. puck+beacon.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

