

CERTIFICATE OF COMPLIANCE

Certificate Number E87056
Report Reference E87056-20171201
Issue Date 2020-SEPTEMBER-02

Issued to: Pepperl+Fuchs AG
Lilienthalstrasse 200
68307 Mannheim GERMANY

**This certificate confirms that
representative samples of** PROXIMITY SWITCHES
See Addendum Page

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-1 & CSA C22.2 No. 60947-1 - Low-Voltage
Switchgear and Controlgear – Part 1: General Rules
UL 60947-5-2 & CSA C22.2 No. 60947-5-2 - Low-voltage
Switchgear and Controlgear - Part 5-2: Control Circuit
Devices and Switching Elements - Proximity Switches

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number E87056
Report Reference E87056-20171201
Issue Date 2020-SEPTEMBER-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Proximity Switches, Cylindrical, Inductive, Class 2 or LV/LC,
Cat. Nos. N, followed by B, C, E, M, R, X, S, H or J, may be followed by B or N, followed by numbers, followed by -numbers, followed by GM, GK, GS, GH, M, K, S or H, may be followed by numbers, followed by -A0, -A2, -E0, -E1, -E2, -E3, -EI, -2E2, -I, -I3, -IU, -N0, -N1, -N, -S1N, -SN, -Z0, -Z1, -Z11, -Z12, -Z13, -Z14, -Z2, -Z3, -Z4, -Z4L or -Z5, may be followed by -IO, may be followed by -C, -C3, -T, -P, -NFE, -NE/FE, -FE, -D, -DW, -150, -200, -250, -M1 or -M, may be followed by -C, -C3, -T, -P, -NFE, -NE/FE, -FE, -D, -DW, -150, -200, -250, -M1 or -M, may be followed by - numbers and M or - numbers and MM, may be followed by -PUR, -PVC or -OG, may be followed by -V1, -V15, -V3 or -V31, may be followed by -3G-3D, -M1, -M or -S2D2, may be followed by -3G-3D, -M1, -M or -S2D2, may be followed by - and any combination of letters and/or numbers, may be followed by -Y and any combination of letters and/or numbers.

Proximity Switches, Cylindrical, Inductive, Class 2 or LV/LC,
Cat. Nos. N, followed by B, C, E, M, R, X, S, H or J, followed by numbers, followed by -numbers, followed by -numbers, followed by -A0, -A2, -E0, -E1, -E2, -E3, -EI, -2E2, -I, -I3, -IU, -N0, -N1, -N, -S1N, -SN, -Z0, -Z1, -Z11, -Z12, -Z13, -Z14, -Z2, -Z3, -Z4, -Z4L or -Z5, may be followed by -IO, may be followed by -G or -E93, may be followed by -D, -910 or -931, may be followed by -D, -910 or -931, may be followed by -D, -910 or -931, may be followed by - numbers and M or - numbers and MM, may be followed by -PUR or -PVC, may be followed by -V1, -V15, -V3 or -V31, may be followed by -3G-3D, may be followed by - and any combination of letters and/or numbers, may be followed by -Y and any combination of letters and/or numbers.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

