

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E501628  
**Report Reference** E501628-20200215  
**Date** 2021-September-17

**Issued to:** Pepperl+Fuchs SE  
Lilienthalstrasse 200  
Mannheim 68307 DE

**This is to certify that  
representative samples of**

AUXILIARY DEVICES FOR USE IN HAZARDOUS  
LOCATIONS

See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** See Addendum for Standards

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E501628  
**Report Reference** E501628-20200215  
**Date** 2021-September-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

USL, CNL – Intrinsically safe apparatus for use in Class I, Division 1 Group A, B, C, D

USL - Class I, Zone 0, AEx ia IIC

CNL - Ex ia IIC Ga

Type code NCN3-F25, may be followed by F, followed by –N4, may be followed by a combination of digits beginning with a hyphen and a numeric digit not relevant to construction differences, -V1 or -Y41364, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

Type code NCN3-F31, followed by –N4 or –N5, followed by -K, -V1, -V16 or -V18, may be followed by a combination of digits beginning with a hyphen and a numeric digit not relevant to construction differences, -K, -V1 or –V16, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

Type code NCN3-F31K, followed by –N4 or –N5, may be followed by -K, -V1, -B13, -B23, may be followed by –K or –V1, may be followed by S, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

USL, CNL - Intrinsically safe apparatus for use in Class I, Division 1 Group A, B, C, D; Class II, Division 1, Group E, F, G; and Class III, Division 1


USL - Class I, Zone 0, AEx ia IIC; Zone 20 AEx ia IIIC

CNL - Ex ia IIC Ga; Ex ia IIIC Da

Type code NCN3-F25, may be followed by F, followed by –N4, may be followed by a combination of digits beginning with a hyphen and a numeric digit not relevant to construction differences, -V1 or -Y41364, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

Type code NCN3-F31–N4, followed by -K, may be followed by a combination of digits beginning with a hyphen and a numeric digit not relevant to construction differences, -K, -V1 or –V16, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

Type code NCN3-F31–N4, followed by -V1, -V16 or -V18, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E501628  
**Report Reference** E501628-20200215  
**Date** 2021-September-17

Type code NCN3-F31K-N4, may be followed by S, may be followed by -Y with up to fifteen digits not relevant to safety characteristics. Intrinsically safe when installed in accordance with control drawing number 116-0456.

**Standard(s) for Safety**


UL 913 STANDARD FOR INTRINSICALLY SAFE APPARATUS AND ASSOCIATED APPARATUS FOR USE IN CLASS I, II, III, DIVISION 1, HAZARDOUS (CLASSIFIED) LOCATIONS

UL 60079-0 EXPLOSIVE ATMOSPHERES - PART 0: EQUIPMENT - GENERAL REQUIREMENTS

UL 60079-11 EXPLOSIVE ATMOSPHERES - PART 11: EQUIPMENT PROTECTION BY INTRINSIC SAFETY 'I'

CSA C22.2 NO. 60079-11:14 EXPLOSIVE ATMOSPHERES — PART 11: EQUIPMENT PROTECTION BY INTRINSIC SAFETY "I"

CSA C22.2 NO. 60079-0 EXPLOSIVE ATMOSPHERES — PART 0: EQUIPMENT — GENERAL REQUIREMENTS



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

