

CERTIFICATE OF COMPLIANCE

Certificate Number 20161215-E106378
Report Reference E106378-20161215
Issue Date 2016-DECEMBER-15

Issued to: Pepperl+Fuchs Inc
1600 ENTERPRISE PKWY
TWINSBURG OH 44087-2202

**This is to certify that
representative samples of**

PROCESS CONTROL EQUIPMENT FOR USE IN
HAZARDOUS LOCATIONS

Refer to Addendum Page for Models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

UL 913, Intrinsically Safe Apparatus And Associated
Apparatus For Use In Class I, II, III, Division 1,
Hazardous (Classified) Locations;
CSA C22.2 NO. 157-92, Intrinsically Safe And Non-
Incendive Equipment For Use In Hazardous Locations;
ISA 12.12.01 and CSA C22.2 NO. 213, Nonincendive
Electrical Equipment For Use In Class I and II, Division 2,
and Class III, Divisions 1 and 2 Hazardous (Classified)
Locations;
UL 61010-1 and CAN/CSA C22.2 No. 61010-1, Electrical
Equipment For Measurement, Control, and Laboratory
Use - Part 1: General Requirements

Additional Information:

See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20161215-E106378
Report Reference E106378-20161215
Issue Date 2016-DECEMBER-15

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

PRODUCT COVERED:


Associated Apparatus,

Model: KFD2 ST(C or V)4-Ex1*, (where * = blank, .H, .2O, .2O.H, -Y(used with C), -1(used with V), -2(used with V) followed by up to 6 numbers or -Y followed by up to 6 numbers); providing intrinsically safe circuits for Division 1, Class I, Groups A, B, C, and D; Class II, Groups E, F, and G, Class III hazardous locations, when installed in accordance with control drawing No. 116-0428.

Model: KFD2-ST(C or V)4-Ex2*, (where * = blank or -Y(used with C), -1(used with V), -2(used with V) followed by up to 6 numbers); providing intrinsically safe circuits for Division 1, Class I, Groups A, B, C, and D; Class II, Groups E, F, and G, Class III hazardous locations, when installed in accordance with control drawing No. 116-0428.

Signal Conditioner,

Models: KFD2-STC4-1, KFD2-STC4-1.20, KFD2-STV4-1-1, KFD2-STV4-2-1, for use in Non-hazardous or Class I, Division 2, Groups A, B, C, and D.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

