



TYPE EXAMINATION CERTIFICATE



Equipment or Protective System intended for use in Potentially Explosive Atmospheres Directive 2014/34/EU

- [3] Type Examination Certificate Number: **UL 22 ATEX 2870X Rev. 0**
- [4] Product: **Vibration Sensors VIM8***-****-2*-***** and VIM8***-****-C*-*******
- [5] Manufacturer: **Pepperl+Fuchs SE**
- [6] Address: **Lilienthalstrasse 200, 68307 Mannheim, Germany**
- [7] This equipment and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.
- [8] UL International Demko A/S certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products intended for use in potentially explosive atmospheres given in Annex II to Directive 2014/34/EU of the European Parliament and of the Council, dated 26 February 2014.
- The examination and test results are recorded in confidential report no. **DK/ULD/ExTR22.0029/00**.
- [9] Compliance with the Essential Health and Safety Requirements has been assured by compliance with:
- EN IEC 60079-0:2018 EN IEC 60079-7: 2015 +A1:2018 EN 60079-31:2014**
- except in respect of those requirements listed at item 18 of the Schedule.
- [10] If the sign "X" is placed after the certificate number, it indicates that the product is subject to the Specific Conditions of Use specified in the schedule to this certificate.
- [11] This Type examination certificate relates only to the design of the specified product, and not to specific items of product subsequently manufactured.
- [12] The marking of the product shall include the following:

 **II 3 G Ex ec IIC T4 Gc**
 **II 3 D Ex tc IIIC T135°C Dc**

Certification Manager
Jan-Erik Storgaard

This is to certify that the sample(s) of the Product described herein ("Certified Product") has been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the ATEX Product Certification Program Requirements. This certificate and test results obtained apply only to the product sample(s) submitted by the Manufacturer. UL did not select the sample(s) or determine whether the sample(s) provided were representative of other manufactured product. UL has not established Follow-Up Service or other surveillance of the product. The Manufacturer is solely and fully responsible for conformity of all product to all applicable Standards, specifications, requirements or Directives. The test results may not be used, in whole or in part, in any other document without UL's prior written approval.

Date of issue: 2022-08-26

Certification Body

UL International Demko A/S, Borupvang 5A, 2750 Ballerup, Denmark
Tel. +45 44 85 65 65, info.dk@ul.com, www.ul.com



[13]

[14]

Schedule TYPE EXAMINATION CERTIFICATE No. UL 22 ATEX 2870X Rev. 0

[15] Description of Product:

Enclosed Type, Vibration Sensor, measuring and monitoring absolute bearing vibrations/temperature in machine.
VIM8***_*****_2*_***** and VIM8***_*****_C*_*****

VIM8***_*****_2*_*****
models VIM8***_**V**_2*_*****, VIM8***_**G**_2*_*****, VIM8***_**C**_2*_***** and
VIM8***_**B**_2*_*****, where x is any number or character.

VIM8***_*****_C*_*****
models VIM8***_**V**_C*_*****, VIM8***_**G**_C*_*****, VIM8***_**C**_C*_***** and
VIM8***_**B**_C*_*****, where x is any number or character.

The VIM8***_**V**_***_***** vibration control is used for measuring and monitoring absolute bearing vibrations in machines. It has one analogue output and two potential-free switching contacts.


The VIM8***_**G**_***_***** vibration control is used for measuring and monitoring vibration acceleration in machines. It has one analogue output and two potential-free switching contacts with window function.

The VIM8***_**C**_***_***** vibration control is used for measuring and monitoring absolute bearing vibrations in machines and provides a bearing status parameter. It has two analogue outputs and two potential-free switching contacts.

The VIM8***_**B**_***_***** vibration control is used for measuring and monitoring vibration acceleration in machines and provides a bearing status parameter. It has two analogue outputs and two potential-free switching contacts with window function.

Temperature range:

The Vibration Sensors VIM8***_*****_2*_*****, VIM8***_*****_C*_***** are for mounting to process lines running adjacent to the enclosure. The temperature of the process line has a temperature range of -40°C to +125°C

Coding		VIM8***_**V**_2*_*****	VIM8***_**V**_C*_*****	VIM8***_**G**_2*_*****	VIM8***_**G**_C*_*****	VIM8***_**C**_2*_*****	VIM8***_**C**_C*_*****	VIM8***_**B**_2*_*****	VIM8***_**B**_C*_*****
Connector	M12 Plug/Socket	x		x		x		x	
	Integrated cable (cable gland)		x	x		x		x	
Measuring head temperature T _M Ambient temperature T _A	-40 °C ≤ T _M ≤ 85 °C -40 °C ≤ T _A ≤ 60 °C	x		x		x		x	
	-35 °C ≤ T _M ≤ 125 °C -35 °C ≤ T _A ≤ 60 °C		x		x		x		x
EX 	II 3G Ex ec IIC T4 Gc II 3D Ex tc IIIC 135°C Dc UL 22 ATEX 2870X	x	x	x	x	x	x	x	x

Electrical data

24±10%Vdc, 100mA; Potential free switching contact 2 x 30Vdc/1.0A;

VIM8***_**V**_***_***** and VIM8***_**G**_***_***** Series:

Analog Output 1 x 4..20mA

VIM8***_**C**_***_***** and VIM8***_**B**_***_***** Series:

Analog Output 2 x 4..20mA



[13]

[14]

Schedule
TYPE EXAMINATION CERTIFICATE No.
UL 22 ATEX 2870X Rev. 0

Routine tests:

N/A

[16]

Descriptive Documents

The scheduled drawings are listed in the report no. provided under item no. [8] on page 1 of this Type Examination Certificate.

[17]

Special Conditions of Use:

- The ambient temperature range is between -40°C and +60°C. The measuring head service temperature range is between -40°C and +125°C. Model differences must be observed.
- Integration of the potential equalization is carried out via installation, see installation instructions for details.
- The cable glands are tested with a reduced tensile force (25 %) in accordance with clause A.3.1 of IEC 60079-0 and may only be used for fixed installation of Group II apparatus. The user shall ensure adequate clamping of the cable.
-

[18]

Essential Health and Safety Requirements

The Essential Health and Safety Requirements (EHSRs) covered by the standards listed at item 9.

Additional information

The Vibration Sensors VIM8***-*****-*2*-***** , VIM8***-*****-*C*-***** have in addition passed the tests for Ingress Protection to IP 66/67 in accordance with EN60529:1991+A1:2000+A2:2013.



The trademark

will be used as the company identifier on the marking label.

