Certificate Number UL-US-2230246-0
Report Reference E87056-20220729

Date 11-Aug-2022

Issued to: Pepperl+Fuchs SE

Lilienthalstrasse 200 Mannheim 68307

Germany

This is to certify that representative samples of

NRKH2 - Proximity Switches - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in contain constructional factures or restricted in

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 60947-5-2, 3rd Ed., Issue Date: 2014-03-28, UL 60947-

1, 5th Ed., Issue Date: 2013-07-31, Revision Date: 2019-

05-06

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.





Bruce Mahrenholz, Director North American Certification Program

Certificate Number UL-US-2230246-0
Report Reference E87056-20220729
Date 11-Aug-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
UC, followed by C or Blank, followed by 2 to 5 digits,	Proximity Switches
followed by -, followed by 2 digits, followed by K, GK,	
M, GM, H, GH, S or GS, followed by –, followed by	
B20, B26 or B followed by 2 digits, Followed by –,	
followed by xM (where x is a decimal number to 2	
decimal place) Or xMOL (where x is a digit) Or Blank,	
Followed by –, followed by V15, V1, V17, V31 or Blank,	
followed by -, May be followed by Yx where x is any	
number of alphanumeric characters.	WILWIL WILWIL W





Certificate Number UL-CA-2229610-0 Report Reference E87056-20220729 Date

11-Aug-2022

Pepperl+Fuchs SE Issued to:

Lilienthalstrasse 200 Mannheim 68307

Germany

This is to certify that representative samples of NRKH8 - Proximity Switches Certified for Canada · Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

CSA C22.2 NO. 60947-1-13, 2nd Ed., Issue Date: 2013-07-Standard(s) for Safety:

31, CSA C22.2 NO. 60947-5-2-14, 1st Ed., Issue Date:

2014-03-28

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.





Certificate Number UL-CA-2229610-0
Report Reference E87056-20220729
Date 11-Aug-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
UC, followed by C or Blank, followed by 2 to 5 digits,	Proximity Switches
followed by -, followed by 2 digits, followed by K, GK,	
M, GM, H, GH, S or GS, followed by –, followed by	
B20, B26 or B followed by 2 digits, Followed by –,	
followed by xM (where x is a decimal number to 2	
decimal place) Or xMOL (where x is a digit) Or Blank,	
Followed by –, followed by V15, V1, V17, V31 or Blank,	
followed by -, May be followed by Yx where x is any	
number of alphanumeric characters.	VII. VII. VII. VII. VI





Bruce Mahrenholz, Director North American Certification Program