

Certificate No: **TAA00003AK** 

# TYPE APPROVAL CERTIFICATE

This is to cer	tify:								
That the Positio	n Switch								
with type designation(s) Inductive proximity switches NB x xx - xx GM xx - xx - xx									
Issued to PepperI+Fuchs SE Mannheim, Baden-Württemberg, Germany									
is found to compl DNV rules for o	ly with classification – Ships, offshore units,	and high speed and light craft							
Application :									
Product(s) appr	oved by this certificate is/are accepte	d for installation on all vessels classed by DNV.							
Location classe	s:								
Temperature Humidity Vibration EMC Enclosure	D В В А D								
Issued at <b>Hamb</b> u	urg on 2023-07-12	for DANY							
This Certificate is DNV local unit: <b>A</b>	s valid until <b>2028-07-11</b> . <b>Lugsburg</b>	for <b>DNV</b>							
Approval Engine	er: <b>Holger Jansen</b>	Joannis Papanuskas Head of Section							

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.

Form code: TA 251

Revision: 2022-12

www.dnv.com

Page 1 of 3



Page 1 of 3

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-037106-1** Certificate No: **TAA00003AK** 

### **Product description**

	[1]	[2]	[3]	[4]		[5]	[6]	[7]	[8]		[9]		[10]
ſ	Ζ	В	Х	XX	-	XX	G	М	XX	-	XX	-	XX

	T	
[1]	N = inductive	
[2]	B = base line	
[3]	B = flush	
	N = non-flush	
[4]	Operating range in mm:	2 up to 30
[5]	Diameter in mm:	12 up to 30
[6]	G = threading	
[7]	M = metal	
[8]	Usable threaded length in mm	30 up to 65
[9]	Electrical output:	A0 = 4-wire, DC, NPN, NO and NC
		A2 = 4-wire, DC, PNP, NO and NC
		E0 = 3-wire, DC, NPN, NO
		E1 = 3-wire, DC, NPN, NC
		E2 = 3-wire, DC, PNP, NO
		E3 = 3-wire, DC, PNP, NC
[10]	Connection type:	_ (blank) = 2m PVC cable
		PUR = 2m PUR cable
		V1 = M12- connector
		xM x=0,1 20 m PVC cable
		xM-V1 x=0,1 20 m PVC cable and M12-connector
		xM-V3 x=0,1 20 m PVC cable and M8-connector
		xM-V31 x=0,1 20 m PVC cable and M8-connector
		xM-PUR x=0,1 20 m PUR cable
		xM-PUR-V1 x=0,1 20 m PUR cable and M12-connector
		xM-PUR-V3 x=0,1 20 m PUR cable and M8-connector
		xM-PUR-V31 x=0,1 20 m PUR cable and M8-connector

#### Place of manufacture

Pepper+Fuchs (Vietnam) Company Limited Lot S12-16A, Street 20 Tan Thuan EPZ Tan Thuan Dong Ward, District 7 Ho Chi Minh City Vietnam

## **Application/Limitation**

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV Rules for Ships Pt.4 Ch.9 Control and Monitoring Systems.

## Type Approval documentation

Data sheets: NBB5-18GM40-E2-V1 dated 2021-09-01

NBN12-18GM30-E2 dated 2021-09-01

Cable 3x034 - Y/YM no. 31-1926+ F dated 2019-05-16

Test reports: No. PRDE-CV26D dated 2023-04-03

No. PRDE-CV69 dated 2022-12-08 No. LAB-222/27 dated 2022-11-17

Drawings: Product qualification plan FE-3395 no. PRDECSN3 2023-02-07

Product description for product family #326161-xxxx and #326163-xxxx

Description "Zylindrischer Näherungsschalter"

Sensor overview DNV 20220201.pdf

Type Approval Assessment Report 2023-05-30

#### **Tests carried out**

Applicable tests according to DNV Class Guideline CG0339, August 2021.

Form code: TA 251 Revision: 2022-12 www.dnv.com Page 2 of 3



Job Id: **262.1-037106-1** Certificate No: **TAA00003AK** 

# Marking of product

The products to be marked with:

- Manufacturer name
- Type designation
- Part no.

#### Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control
  routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- · Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

**END OF CERTIFICATE** 

Form code: TA 251 Revision: 2022-12 www.dnv.com Page 3 of 3