





THIS CERTIFICATE IS ISSUED AS AN I.A. CERTIFICATE IN TERMS OF THE MINE HEALTH AND SAFETY ACT, ACT NO 29 OF 1996 (AND REGULATIONS), THE OCCUPATIONAL HEALTH AND SAFETY ACT (ACT 85 OF 1993) AND REGULATION 17 OF THE ELECTRICAL MACHINERY REGULATIONS

| | MASC MS/23-8422X | Issue | 0 | |
|--|---|---|---|--|
| Issue Date ** Based on Certificate No | 5 September 2023 IECEx BVS 13.0119X | Expiry Date | 23 July 2024 ns / Amendment 2 | |
| Requested by | IECEx BVS 13.0119X Issue / Variations / Amendment 2 Pepperl+Fuchs (Pty) Ltd | | | |
| | Zerwick Forum, 8 Glen Eagle Office Park Cnr Monument Rd and Braambos St, Glen Erasmia, Kempton Park 1619, South Africa | | | |
| Manufacturer | Pepperl+Fuchs SE Lilienthalstrasse 200, 68307 Mannheim, Germany | | | |
| Description | The 8-channel (R4D0-FB-IA8), 10-channel (R4D0-FB-IA10) and 12-channel (R4D0-FB-IA12) | | | |
| | Fieldbus Barriers are galvanically isolated fieldbus couplers for the supply of intrinsically safe field devices and the bidirectional transmission of the fieldbus signals. The up to 12 outputs are intrinsically safe, with level of protection "Ex ia I", "Ex ia IIC" resp. "Ex ia IIIC", and can be led in areas requiring EPL Ma, Ga resp. Da. The intrinsically safe outputs are designed to be used in accordance with the Entity- and FISCO concept. On the trunk side the Fieldbus Barrier is supplied by a non-intrinsically safe circuit. The trunk connection for the supply is doubled to be able to loop through the supply voltage to the next unit. Maximum 3 Fieldbus Barriers may be connected to the trunk. The non-intrinsically safe circuits are protected by type of protection Increased Safety "Ex eb" and encapsulation "Ex mb" and fulfil the requirements of EPL Gb. The Fieldbus Barrier is intended to be mounted into an enclosure type of protection Increased Safety resp. into a suitable, separately certified enclosure. | | | |
| Equipment | See Base Certificate** for par Fieldbus Barrier | | D-FB-IA* | |
| MARKING: | Type: | | type R4D0-FB-IA* | |
| Original marking as per certificate ** remains applicable. | Ex Marking: | Ex eb ib mb [ia Ga] IIC T4 Gb [Ex ia Da] IIIC [Ex ia Ma] I | | |
| IA number must be added. | IA Number: Warnings: | MASC MS/23-8 See Base Certif | 422X (To be additionally marked on equipment) icate ** (original marking must be applied) | |
| Quality Assurance report (Q | AR) / Notification (QAN): | DE/PTB/QAR06 | | |
| Quality Assurance report (Q | (QAN) / Notification (QAN) | 23 July 2024 | | |
| Expiry date: Compliance: | | | | |
| | ensure that the product complie ise "X": | ion by increased s ion by intrinsic saf ion by encapsulati bes not imply com | ety "i" on "m" pliance to any other standard, related or inferred. It | |
| Conditions of manufacture: | | | | |
| Refer to Annex A below feedback | or more details. | | | |
| C. WELTHAGEN TECHNICAL SPECIALIST TECHNICAL OFFICER | | | Stitjoen. | |
| | This certificate covers all units s | uction units of explosion | QAN remains valid. protected equipment are required to comply with third party quality | |
| | Any conditions men Any restrictions and conditions enfo inspector (Group I equipment) or ch This certificate ma The certificate is not transferable a Mining And Surf Unit 5 Lelyta Park, 45 J | which shall be adhere 0.86 requirements; tioned in the above c juirements of the MH3 reced by the chief insp ief inspector of factor ay only be reproduced and remains the properties face Certification (Pty | d to: ertificate; SAct; bector of mines, principal ries (Group II equipment). d in full erty of the issuing body. r) Ltd | |

IA CERTIFICATE: MASC MS/23-8422X Equipment: Fieldbus Barrier

(Expiry date: 23 July 2024)

Page 2 of 2

ANNEX A

| This | document is based on and must be read in conjunction with certificate IECEx BVS 13.0119X. | | |
|--|--|--|--|
| Description (According to Base Certificate) ** "Refer to description in Base Certificate ** (and any applicable schedules/issues/variations)." | | | |
| | | | |
| Special conditions of safe use ("X") | The Fieldbus Barrier has to be mounted into a suitable, separately certified enclosure. The temperature inside the enclosure shall not exceed the permissible ambient temperature of the Fieldbus Barrier. The external enclosure has to carry the warning "WARNING – NON-INTRINSICALLY SAFE CIRCUITS PROTECTED BY INTERNAL IP30 COVER" | | |
| Conditions of manufacture | None. | | |
| Conditions of Certification | This IA Certificate covers all units sold from the date of this document to the expiry date of this certificate. As per ARP 0108 a maximum three yearly review is required on this IA Certificate (expiry is determined as per the QAR/QAN/QMS expiry date). The apparatus must be additionally marked with the MASC marking details above. This approval only covers the equipment as certified above and does not include any scheduled additions or variations / amendments / new issues to the certificate(s), made after the above date. The equipment does not need to be re-tested when used on the conditions and with such restrictions as prescribed by the certificate on which this IA Certificate is based and any other conditions in this IA Certificate. The certification on which this IA Certificate is based must remain valid. The extent of the requirements in the ARP 0108 (or regulations), SANS 10108 and any other applicable regulations on the certification of the equipment must remain unchanged. The Ex-quality assurance notification/report for the equipment must remain valid. | | |
| Conclusion: | From the above and the selective examination of the documentation, nothing contrary to the requirements of the applicable standards was found, provided that the equipment / component is used as described in the above document / certificate and according to the MASC conditions below. A MASC IA certificate is issued based on the work done as per the Base Certificate **. The routine tests for production units according to the Base Certificate ** must be complied with (if applicable). | | |

This document is issued based on Mining And Surface Certification's Standard Contract terms and conditions available on request.

While every endeavour is made to ensure that a test / assessment / inspection is representative and accurately performed, and that a report / certificate is accurate in the quoted results and conclusions drawn from the test / assessment / inspection, MASC or its directors/employees shall in no way be liable for any error made in carrying out the test / assessment or in option, statement, whether in fact or in option, contained in a report / certificate is pursuant to a test / inspection.

MASC takes no responsibility for any non-conformances, exclusions, or any results / assessments / inspections not in compliance with the standards. By marking the equipment in accordance with the documentation / standard, the manufacturer / applicant attests on his own responsibility that the equipment / installation has been designed and constructed in accordance with the applicable requirements of the relevant standards and documentation, that the routine verifications / routine tests have been correctly completed and the equipment / installation complies with the documentation and standard(s).

This document is only for use and application in South Africa. It is issued based on National interpretations and accepted practices.

This document may only be reproduced in full. This certificate is not transferable and remains the property of the issuing body. This document will not be supported by MASC for certification purposes outside the borders of South Africa.