

Certificate of Compliance

Certificate Number(s):

UL-US-2401419-1

Report Reference:

E501881-20210517

Issue Date:

2026-06-25

Issued to:

Pepperl+Fuchs SE
Lilienthalstrasse 200, Mannheim, 68307, DE

This certificate confirms that representative samples of:

QVSI - Isolated Loop Circuit Protectors for Use in Hazardous Locations

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 913, Edition 8, Issue Date 2013-12-06, Revision Date 2022-05-10

UL 121201, 9th Ed., Issue Date: 2017-09-15, Revision Date: 2021-04-01

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-US-2401419-1
Report reference: E501881-20210517
Issue Date: 2026-06-25

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Class I, Division 1, Group A, B, C and D, Class I, Division 2, Group A, B, C and D, when installed in accordance with Control Drawing No(s). 116-0479A, Surge Protection Barriers

M-LB, Model(s): M-LB-Ex-21 followed by 1 or 4, followed by 2 or 4, may be followed by SP, may be followed by any digits or symbols specifying properties without safety relevance.

Class I, Division 2, Group A, B, C and D, Surge Protection Barriers, open type for use in a tool secured enclosure,

M-LB, Model(s): M-LB-21 followed by 1 or 4, followed by 2 or 4, may be followed by .SP, may be followed by any digits or symbols specifying properties without safety relevance.

Class I, Division 1, Group A, B, C and D, Class I, Division 2, Group A, B, C and D, when installed in accordance with Control Drawing No(s). 116-0510, Surge Protection Barriers

M-LB, Model(s): M-LB-Ex-26 followed by 1 or 4, followed by 5 or 6, may be followed by any digits or symbols specifying properties without safety relevance

Class I, Division 2, Group A, B, C and D, Surge Protection Barriers

M-LB, Model(s): M-LB-26 followed by 1 or 4, followed by 5 or 6, may be followed by any digits or symbols specifying properties without safety relevance