

Pepperl+Fuchs SE
Lilienthalstraße 200
68307 Mannheim
Germany
Phone +49 621 776-0
Fax +49 621 776-1000

No. / Nr.: DOC-4653A
Date / Datum: 2022-10-14

Copyright Pepperl+Fuchs
www.pepperl-fuchs.com



Declaration of conformity / Konformitätserklärung

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **European Directives** and **standards**.

Die Pepperl+Fuchs SE erklärt hiermit in alleiniger Verantwortung, dass die unten gelisteten **Produkte** den genannten **Europäischen Richtlinien** und **Normen** entsprechen.

Product Family

Product Family	Description
VOSxxxxy-Fxxxxy-xxxx-x	Vision Sensor

The „x,y“ marked letters of the type code are placeholders and can be replaced by the code described in ANNEX TYPE CODE.

Directives and Standards / Richtlinien und Normen

EU-Directive EU-Richtlinie	Standards Normen
EMC 2014/30/EU (L96/79-106)	EN 55011/A11:2020-03 EN 55011:2016-04 EN 55032/A11:2020-03 EN 55032:2015-07 EN 55035:2017-07 EN 61326-1:2013-01
RoHS 2011/65/EU (L174/88-110)	EN IEC 63000:2018-12

Affixed CE Marking / Angebrachte CE-Kennzeichnung



Signatures / Unterschriften

Mannheim, 2022-10-14

i.V. Hilmar Hofmann
RnD Manager Business Unit Industrial
Vision Components

i.V. Markus Karch
Product Manager Business Unit Industrial
Vision Components

■ ANNEX TYPE CODE

The „x,y“ marked letters of the type code are placeholders and can be replaced by the following code:

Die mit "x,y" gekennzeichneten Buchstaben des Typencodes sind Platzhalter und können durch den folgenden Code ersetzt werden:

VOSxxxxy-Fxxxxy-xxxx-x								
xxxx Resolution Auflösung		y Image Sensor Bildsensor	Fxxx Housing Variant Gehäusevariante	y Light Color Lichtfarbe	xxxx Focal length Brennweite		x Firmware	
1000	640x480	/ Monochrome C Color	F226 Standard w. two connectors	/	no integrated light	6MM	integrated lens with 6mm	S Standard I Ident
2000	1280x960		F227 Large w. three connectors	W	integrated light white LED	8MM	integrated lens with 8mm	
5000	2560x2048		R	integrated light red LED	12MM	integrated lens with 12mm		
			B	integrated light blue LED	16MM	integrated lens with 16mm		
			I	integrated light infrared LED	C	C-Mount		
				U	integrated light UV LED			