

Pepperl+Fuchs SE
Lilienthalstraße 200
68307 Mannheim
Germany
Phone +49 621 776-0
Fax +49 621 776-1000

No. / Nr.: DOC-5035
Date / Datum: 2023-09-12

Copyright Pepperl+Fuchs
www.pepperl-fuchs.com



Declaration of conformity / Konformitätserklärung

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **European Directives** and **standards**.

Die Pepperl+Fuchs SE erklärt hiermit in alleiniger Verantwortung, dass die unten gelisteten **Produkte** den genannten **Europäischen Richtlinien** und **Normen** entsprechen.

Product family / Produktfamilie

Product / Produkt	Description / Beschreibung
VMa-b-d-eM-f-g	Valve connector

The "a", "b", "d", "e", "f" and "g" marked letters of the type code are placeholders and can be replaced by the code described in ANNEX TYPE CODE.

Die mit "a", "b", "d", "e", "f" und "g" markierten Stellen im Typenschlüssel sind Platzhalter und können durch den Schlüssel ersetzt werden der in ANNEX TYPE CODE beschrieben ist.

Directives and Standards / Richtlinien und Normen

EU-Directive EU-Richtlinie	Standards Normen
2011/65/EU (RoHS) (L174/88-110)	EN IEC 63000:2018-12

Affixed CE Marking / Angebrachte CE-Kennzeichnung



Signatures / Unterschriften

Mannheim, 2023-09-12

ppa. Sebastian Stöber
Vice President Business Unit Systems

i.V. Simon Wagner
Product Manager

ANNEX TYPE CODE

The "a", "b", "d", "e", "f" and "g" marked letters of the type code are placeholders and can be replaced by the following code:

Die mit "a", "b", "d", "e", "f" und "g" markierten Stellen im Typenschlüssel sind Platzhalter und können durch folgenden Schlüssel ersetzt werden:

VMa-b-d-eM-f-g	
VM	Valve connector
a	A=Valve connector A; B=Valve connector B; BI=Valve connector B industrial; C= Valve connector C; CI= Valve connector C industrial
b	2+P/Z2 = Number of pins 2 + PE with Z diode; 2+PR/Z2 = Number of pins 2 + PE 180° with LED and Z diode; 2+P/A = Number of pins 2 + PE with amplifier; 2+P/D2 = Number of pins 2 + PE with damping diode; 3+P/L1 = Number of pins 2 + PE with LED and Z diode
d	Color (blank = Grey; BK = Black; BL = Blue; BN = Brown; GN = Green; YE = Yellow; OR = Orange; RD = Red; VT = Violet; WT = White) + length in m
e	Jacket Material (PUR; PVC; PUR-U; PUR-U/ABG; PVC-U; PUR-U/0,75; PUR-O1; PUR-O2; PUR-O3; POC)
f	V1-G = M12 4-pin A-coded male straight connector; V1-W = M12 4-pin A-coded male angled connector; V1-GV4A = M12 4-pin A-coded male straight connector with stainless steel screw; V1-WV4A= M12 4-pin A-coded male angled connector with stainless steel screw
g	blank = Standard; Y followed by any number = Special version