en

Pepperl+Fuchs SE Lilienthalstrasse 200 68307 Mannheim Germany Phone +49 621 776-0 Fax +49 621 776-1000

Copyright Pepperl+Fuchs www.pepperl-fuchs.com

**EPPERL+FUCHS** 

No: DOC-5875

Date: 2022-05-25

### Declaration of conformity

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **UK Regulations** as indicated below and amended by **UK SI 2019 No. 696**, and **standards**.

## Product family

Product	Description
V1S-a-b-c-dM-e-g	Male cordset, 4-pin M12 connector

The "a", "c", "d", "e" and "g" marked letters of the type code are placeholders and can be replaced by the code described in ANNEX TYPE CODE.

### Regulations and Standards

UK Regulation	Standards
UK SI 2012 No. 3032 (RoHS)	EN IEC 63000:2018-12
UK SI 2016 No. 1101 (LV)	EN 61010-1:2010-10

# Affixed UKCA Marking



### Signatures

Mannheim, 2022-05-25

i.V. Sebastian Stöber Executive Vice President Business Unit Systems i.V. Wolfram Warnecke

Approval Engineer

#### ANNEX TYPE CODE

The "a", "c", "d", "e" and "g" marked letters of the type code are place-holders and can be replaced by the following code:

V1S-a	V1S-a-b-c-dM-e-g	
V1S	Connector type	
а	G = Straight; W = Angled; GV4A = Straight stainless steel nut; WV4A = Angled stainless steel nut; GU = Straight Ultralock; WU = Angled Ultralock; GT = Straight Teflon; WT = Angled Teflon; GX = Straight XXL head, WX = Angled XXL head	
b	N= NAMUR 2-pin; N4= NAMUR 4-pin	
С	Blank = Standard; GN = Green connector head; GY = Grey connector head; S = Safety, Yellow connector head; B = Bridged	
d	Color (blank = Grey; BK = Black; BL = Blue; BN = Brown; GN = Green; YE = Yellow; OR = Orange; RD = Red; VT = Violet; WT = White) + length in m	
е	Jacket Material (PUR; PVC; PUR-U; PUR-U/ABG; PUR-U5/ABG; PVC-U; PUR-U/0,75; PUR-ABG; PVC-ABG; PUR-A; PUR-R1; PUR-R2; PUR-R3; PUR-O1; PUR-O2; PUR-O3; POC; PUR-O15; PUR-O25; PUR-O35; TPE; PP; PUR-E1, PUR-E2; PUR-E3; PUR-E15; PUR-E25; PUR-E35; PUR-CAN; PUR-U/CAN; PUR-N15; PUR-N25; PUR-N35)	
g	blank = Standard; Y followed by any number = Special version	

DOC-5875 / 2022-05-25 1/1