en

Pepperl+Fuchs SE Lilienthalstrasse 200 68307 Mannheim Germany Phone +49 621 776-0 Fax +49 621 776-1000

Copyright Pepperl+Fuchs www.pepperl-fuchs.com

5PEPPERL+FUCHS

No: DOC-5892

Date: 2022-08-02

Declaration of conformity

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **UK Regulations** as indicated below and amended by **UK SI 2019 No. 696**, and **standards**.

Product family

Product	Description
V1SD-a-c-dM-e-g	Male cordset, 4-pin M12 connector

The "a", "c", "d", "e" and "g" marked letters of the type code are place-holders and can be replaced by the code described in ANNEX TYPE CODE.

Regulations and Standards

UK Regulation	Standards
UK SI 2012 No. 3032 (RoHS)	EN IEC 63000:2018-12

Supplemental Standards	Remarks
IEC 61076-2-101:2012	Connectors for electronic equipment - Product requirements - Part 2-101: Cir- cular connectors - Detail specification for M12 connectors with screw-locking

Affixed UKCA Marking



Signatures

Unit Systems

Mannheim, 2022-08-02

i.V. Sebastian Stöber Executive Vice President Business i. V. lloumbe

i.V. Wolfram Warnecke

Approval Engineer

ANNEX TYPE CODE

The "a", "b", "c", "d", "e" and "g" marked letters of the type code are placeholders and can be replaced by the following code:

V1SD-	V1SD-a-c-dM-e-g	
V1SD	Connector type	
а	G = Straight; W = Angled; GV4A = Straight stainless steel nut; WV4A = Angled stainless steel nut; GU = Straight Ultralock; WU = Angled Ultralock; GT = Straight Teflon; WT = Angled Teflon	
С	Blank = Standard; GN = Green connector head; GY = Grey connector head; S = Safety, Yellow connector head; B = Bridged, X = XXL Head	
d	Color (blank = Grey; BK = Black; BL = Blue; BN = Brown; GN = Green; YE = Yellow; OR = Orange; RD = Red; VT = Violet; WT = White) + length in m	
е	Jacket Material (PUR; PVC; PUR-U; PUR-U/ABG; PUR-U5/ABG; PVC-U; PUR-U/0,75; PUR-ABG; PVC-ABG; PUR-A; PUR-R1; PUR-R2; PUR-R3; PUR-O1; PUR-O2; PUR-O3; POC; PUR-O1S; PUR-O2S; PUR-O3S; TPE; PP; PUR-E1, PUR-E2; PUR-E3; PUR-E1S; PUR-E2S; PUR-E3S)	
g	blank = Standard; Y followed by any number = Special version	