

Pepperl+Fuchs SE
Lilienthalstrasse 200
68307 Mannheim
Germany
Phone +49 621 776-0
Fax +49 621 776-1000

No: DOC-6622
Date: 2022-07-14

Copyright Pepperl+Fuchs
www.pepperl-fuchs.com



Declaration of conformity

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **UK Regulations** as indicated below and amended by **UK SI 2019 No. 696**, and **standards**.

Product Family

| Product Family | Description |
|------------------------|-------------------|
| PHAUuu-F200v-Rw-x-yyyy | Vision 2-D Sensor |

The „u,v,w,x,y“ marked letters of the type code are placeholders and can be replaced by the code described in ANNEX TYPE CODE.

Regulations and Standards

| UK Regulation | Standards |
|----------------------------|---|
| UK SI 2012 No. 3032 (RoHS) | EN IEC 63000:2018-12 |
| UK SI 2016 No. 1091 (EMC) | EN 55011:2016-04 EN 61000-6-4/A1:2011-02 EN 61000-6-4:2007-01 EN 61326-1:2013-01 |

Affixed UKCA Marking



Signatures

Mannheim, 2022-07-14

i.V. Hilmar Hofmann

RnD Manager Business Unit Industrial
Vision Components

i.V. Armin Hornberger

Head of Global Product Management
Business Unit Industrial Vision
Components

■ ANNEX TYPE CODE

The „u,v,w,x,y“ marked letters of the type code are placeholders and can be replaced by the following code:

| PHAuuu-F200v-Rw-x-yyyy | | | | |
|-------------------------------|----------------------------|----------------------|-------------------|---------------------------------|
| u = Working Distance | v = Housing Variant | w = Interface | x = Option | yyyy = Customer Specific |
| 150 – mm Distance | F200 – Mounting 90° | R2 – RS232 | T - Temperature | |
| 200 – mm Distance | F200A – Mounting 180° | R3 – RS422 | | |
| 250 – mm Distance | | R4 – RS485 | | |
| 300 – mm Distance | | | | |
| 350 – mm Distance | | | | |
| 400 – mm Distance | | | | |
| 500 – mm Distance | | | | |
| 600 – mm Distance | | | | |
| 650 – mm Distance | | | | |
| 950 – mm Distance | | | | |