en

Pepperl+Fuchs SE Lilienthalstrasse 200 68307 Mannheim Germany Phone +49 621 776-0 Fax +49 621 776-1000

Copyright Pepperl+Fuchs
www.pepperl-fuchs.com

FPEPPERL+FUCHS

No: DOC-6750

Date: 2022-09-13

Declaration of conformity

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **UK Regulations** as indicated below and amended by **UK SI 2019 No. 696**, and **standards**.

Product family

Product	Description
V15L-a-c-dM-e-V15L-f-g	Connecting cable, M12 to M12 connector

The "a", "c", "d", "e", "f" and "g" marked letters of the type code are placeholders and can be replaced by the code described in ANNEX TYPE CODE.

Regulations and Standards

UK Regulation	Standards
UK SI 2012 No. 3032 (RoHS)	EN IEC 63000:2018-12

Affixed UKCA Marking



Signatures

Mannheim, 2022-09-13

i.V. Sebastian Stöber Executive Vice President Business Unit Systems i.V. Simon Wagner
Product Manager

ANNEX TYPE CODE

The "a", "c", "d", "e", "f" and "g" marked letters of the type code are placeholders and can be replaced by the following code:

V15L-a	V15L-a-c-dM-e-V15L-f-g	
V15L	Connector type	
a, f	G = Straight; W = Angled	
С	Blank = Standard; 4-pole; GN = Green connector head; GY = Grey connector head; S = Safety, Yellow connector head	
d	Color (blank = Grey; BK = Black; BL = Blue; BN = Brown; GN = Green; YE = Yellow; OR = Orange; RD = Red; VT = Violet; WT = White) + length in m	
е	Jacket Material (PUR; PVC; PUR-U; PUR-U/ABG; PUR-U5/ABG; PVC-U; PUR-U/0,75; PUR-ABG; PVC-ABG; PUR-A; PUR-R1; PUR-R2; PUR-R3; PUR-O1; PUR-O2; PUR-O3; POC; PUR-O1S; PUR-O2S; PUR-O3S; TPE; PP; PUR-E1, PUR-E2; PUR-E3; PUR-E1S; PUR-E2S; PUR-E3S)	
g	blank = standard; Y followed by any number = special version	