

Pepperl+Fuchs SE
Lilienthalstraße 200
68307 Mannheim
Germany
Phone +49 621 776-0
Fax +49 621 776-1000

No.: DOC-6240A
Date: 2023-01-23

Copyright Pepperl+Fuchs
www.pepperl-fuchs.com



■ Declaration of conformity

We, Pepperl+Fuchs SE declare under our sole responsibility that the **products** listed below are in conformity with the listed **UK Regulations** as indicated below and amended by **UK SI 2019 No. 696**, and **standards**.

■ Productfamily

Productfamily	Item number	Description
Prod.Fam. NR*-12/18/30G*-*	306533-xxxx	Inductive sensor

The „X“ marked letters of the type code are placeholders and replaced by the code described in ANNEX TYPE CODE.

■ Regulations and Standards

UK Regulation	Standards
UK SI 2012 No. 3032 (RoHS)	EN IEC 63000:2018-12
UK SI 2016 No. 1091 (EMC)	EN IEC 60947-5-2:2020-03

■ Affixed UKCA Marking



■ Signatures

Mannheim, 2023-01-23

i.V. Ulrich Ehrenfried
Manager Innovation Unit
Electromagnetic Sensors

i.V. Thorsten Schieck
Product Manager
Electromagnetic Sensors

ANNEX TYPE CODE

The „X“ marked letters of the type code are placeholders and replaced by the following code:

NRxx-xxxxxx-xx-xx-x-xxx-xx										
NR	x	x	- xx	xx	xx	- xx	- xx	- x	- xxx	- xx
Inductive sensor	Installation conditions B - flush N - non-flush	Nominal sensing range in mm	Sensor diameter 12 - 12mm 18 - 18mm 30 - 30mm	Housing GM -threaded metal sleeve GS -threaded metal V2A sleeve GH -threaded metal V4A sleeve	Housing length, front face to end of thread in mm	Output stage E0 - 3-Wire DC NPN NO E1 - 3-Wire DC NPN NC E2 - 3-Wire DC PNP NO E3 - 3-Wire DC PNP NC E34 - 3-Wire DC PNP NC (Pin 4) A0 - 4-Wire DC NPN complimentary NO/NC A2 - 4-Wire DC PNP complimentary NO/NC	IO-Link	Special features C - weld immune	Cable length in m, if deviating to standard 2m, e.g. (5M - 5m) (10M - 10m)	Connector V1 - M12 Connector
							<i>Omitted if not applicable</i>	<i>Omitted if not applicable</i>	<i>Omitted if not applicable</i>	<i>Omitted if not applicable</i>