


**Model Number**

NBB5-18GM50-E2-V1-M

Features

- Basic series
- 5 mm embeddable
- e1-Type approval

Connection**Accessories****BF 18**

Mounting flange

V1-G

Non pre-wired cable socket

V1-W

Non pre-wired cable socket

V1-G-2M-PUR


Cable connector

V1-W-2M-PUR

Cable connector

EXG-18

Mounting aid

Dimensions**Technical Data****General specifications**

Switching element function	PNP	Make function
Rated operating distance	s_n	5 mm
Installation		embeddable
Output polarity		DC
Assured operating distance	s_a	0 ... 4.05 mm
Reduction factor r_{Al}		0.3
Reduction factor r_{Cu}		0.3
Reduction factor r_{V2A}		0.7
Reduction factor r_{SI37}		

Nominal ratings

Operating voltage	U_B	10 ... 30 V
Switching frequency	f	0 ... 800 Hz
Reverse polarity protection		protected against reverse polarity
Short-circuit protection		pulsing
Voltage drop	U_d	≤ 3 V
Operating current	I_L	0 ... 200 mA
Off-state current	I_r	0 ... 0.5 mA typ. 0.1 μ A at 25 °C
No-load supply current	I_0	≤ 20 mA
Indication of the switching state		Multihole-LED, yellow

Standard conformity

Standards	IEC / EN 60947-5-2:2004
-----------	-------------------------

Ambient conditions

Ambient temperature	-25 ... 70 °C (248 ... 343 K)
---------------------	-------------------------------

Mechanical specifications

Connection type	V1-connector
Housing material	brass, nickel-plated
Sensing face	PBT
Protection degree	IP67

Approvals and certificates

e1 Type approval	95/54/EC
------------------	----------