

Terminal Block with Test Plug Socket KF-STP-5GN


- 3-pin screw terminal
- For KF modules of K-System
- Integrated test sockets for connection of HART communicators
- Packaging unit: 5 pieces green

Terminal block for KF modules, 3-pin screw terminal, with test sockets, green

Function

The terminal block is suitable for KSystem applications.
 The green terminal block is used for connection of field signals as well as the connection of control signals.
 This terminal block has integrated test sockets for connection of HART communicators.
 The terminal block can be coded with the provided coding pins KF-CP.

Dimensions



Technical Data

General specifications	
Number of pins	3
Mechanical specifications	
Core cross-section	max. 2.5 mm ²
Material	
Color	green
Mass	approx. 5 g
Dimensions	15.1 x 15 x 21 mm (0.6 x 0.6 x 0.83 inch)
Construction type	screw terminal with integrated test sockets , removable
Structure	one-rowed
General information	
Packing unit	5 item(s)

Release date: 2021-08-30 Date of issue: 2021-08-30 Filename: 215364_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

Safety Information

The insulation of the removable terminal blocks protect against direct contact. The insulation conforms to a reinforced insulation acc. to EN 50178 with a rated insulation voltage of 50 V AC.

If the rated voltage greater than 50 V AC, proceed as follows:

- Switch off the voltage.
- Connect the terminal blocks or disconnect the terminal blocks.