

Profile Rail K-DUCT-GY-UPR-03

- Cable trunking with integrated Power Rail UPR-03
- Safe spacious separation of field and control signals
- No additional cable guides necessary
- Provides DC supply voltage to all equipped K-System modules
- Standard length 1.8 m (5.8 ft), simple to customize to application space
- With end caps UPR-E, cover and mounting aids

Profile rail with UPR-03-* insert, 3 conductors, wiring comb field side, gray


Function

The profile rail can be used to provide space-saving mounting for interface modules and accommodate the associated wiring. The system and field cables are easily installed in the integral cable ducts of the profile rail. Thus no additional cable guides are necessary.

The power supply to the individual modules is preferably provided via the Power Rail UPR-03 that is integrated into the system. Additionally the Power Rail UPR-03 has one lead for collective error messaging.

The asymmetrical segmented connection compartment can be changed dependent on the required space by turning the profile rail. Please note that the Power Rail insert must be also rotated. In conjunction with K-System modules the profile rail can be mounted in Zone 2.

Dimensions



Technical Data

Release date: 2023-11-30 Date of issue: 2023-11-30 Filename: 217224_eng.pdf

Mechanical specifications			
Connection	3 condu	luctors	
Field side	wiring c	comb, grey	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information"

Technical Data Control side wiring comb, grey Supply 2 Conductors 1 Conductors Fault output profile rail: aluminum wiring comb: plastic Material Mass approx. 7.3 kg **Dimensions** 130 x 115.8 x 1800 mm (5 x 4.56 x 71 inch) Accessories provided accessories: - end caps UPR-E - cover - mounting aids (glide nuts and glide nut retainers) Designation

5 PEPPERL+FUCHS