LED Contact Module Ex e, 1 Pole, Base-mounted

CFP.I.SP

- Contact block 1x NO
- Component for appropriately certified Ex e enclosures
- Mounting on enclosure base
- DIN rail mountable
- Ex de certified
- Polyamide

Connection

For complete wiring diagram see combination of actuator head and contact module.



Dimensions





Dimension values see data table.
Image and drawing are generic for this device type and may deviate from the specific variant.

Technical Data

Electrical specifications		
Operating voltage		30 V max. AC/DC
Operating current		10 A max.
Power consumption		1 W
Terminal capacity		2.5 mm²
Terminal torque		0.8 Nm
Function		Illuminated pushbutton module

Release date: 2026-02-09 Date of issue: 2026-02-09 Filename: 290212_eng.pdf

Technical Data

Contact configuration	1x NO
Usage category	AC15: 20 ... 250 V AC - 10 A DC13: 20 ... 24 V DC - 1 A
Number of poles	1
Mechanical specifications	
Degree of protection	IP20
Material	
Housing	Polyamide (PA)
Mass	72 g
Mechanical life	300000 switching operations
Dimensions	
External dimension (A)	63 mm
External dimension (B)	33.4 mm
External dimension (C)	47 mm
Mounting holes distance (G)	52 mm
DIN mounting rail receptacle (G3)	35.6 mm
Mounting holes distance (H)	18 mm
Mounting holes diameter (J)	4.2 mm
Thickness of mounting brackets (N)	8 mm
Total length (L)	82 mm
Mounting	base-mounted DIN rail mounting
Ambient conditions	
Ambient temperature	-55 ... 55 °C (-67 ... 131 °F)
Service temperature	-55 ... 85 °C (-67 ... 185 °F)
Data for application in connection with hazardous areas	
EU-type examination certificate	CML 16 ATEX 3339U
Marking	Ⓔx II 2 G Ex de IIC Gb
International approvals	
IECEx approval	IECEx CML 16.0114U
Conformity	
Degree of protection	EN 60529
Usage category	IEC / EN 60947
General information	
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com.
Enclosure type	LR* GR.CS*

Release date: 2026-02-09 Date of issue: 2026-02-09 Filename: 290212_eng.pdf