



Stopping Plugs, Metal, Hexagon Socket Head

SP.MA.NPT1/2.BN.X.20.K01

- Stopping plug for unused cable entries
- Brass nickel-plated
- Thread NPT 1/2"
- Without head, installation by means of allen key
- Ex db, Ex eb and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 1 piece, kit with accessories














Dimensions



Details see data table

Legend		
1	Stopping plug	
KS	Key size	
L	Total length	
TD	Thread size	
TL	Thread length	

Technical Data

Mechanical specifications		
Thread type	NPT ANSI ASME B1.20.1	
Thread size (TD)	NPT 1/2"	
Degree of protection	IP66 / IP68 , UL Type 4X	
Material		

Technical Data	
Finish	inherent color silver
Stopping plug	brass, nickel-plated
Mass	
Individual component	approx. 42 g
Packing unit	approx. 52 g
Dimensions	
Thread length (TL)	20 mm
Total length (L)	20 mm
Key size (KS)	10 mm
Tightening torque	
Nut torque at enclosure (SW1)	8 Nm
Ambient conditions	
Ambient temperature	-60 130 °C (-76 266 °F)
Data for application in connection with haza	rdous areas
EU-type examination certificate	CESI 15 ATEX 029X
Marking	Il 2 GD Ex db IIC Gb Ex eb IIC Gb Ex tb IIIC Db
International approvals	
UL approval	
cULus	E305142 tested to UL 50E and UL 508A CSA C22.2, No. 14-13
IECEx approval	IECEx CES 15.0006X
UKCA approval	CML 22 UKEX 1267X
CCC approval	2021312313000343
Conformity	
Degree of protection	EN 60529
General information	
Delivery quantity	1
Scope of delivery	Stopping Plugs, Metal Brief instructions
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com.

5PEPPERL+FUCHS