


Event marker PCV-CM20-046-001-SET

High chemical resistance

- Low weight
- Self-adhesive mounting
- High temperature resistance
- High mechanical stability

Event markers for the PCV system

Dimensions




Technical Data

General specifications		
Start marker number	46	
Number	1	
Length	1 m per event marker number	
Width	25 mm (2 row version)	
Ambient conditions		
Operating temperature	-40 100 °C (-40 212 °F)	
Installation temperature	10 40 °C (50 104 °F)	
Environmental resistance	UV radiation Humidity Salt spray (150 h / 5%)	
Chemical resistance	Oils Grease Fuels Aliphatic solvents Weak acids	
Mechanical specifications		
Material thickness	150 μm	
Material	polyester laminate	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information"

Pepperl+Fuchs Group www.pepperl-fuchs.com



PCV-CM20-046-001-SET

Event marker

Technical Data

Surface	polyester , matte
Mass	6.3 g / m
Tensile strength	≥ 150 N
Manufacturing tolerance	± 1 mm/m
Adhesive	Acrylate-based adhesive ; curing 72 h
Adhesive strength	Average values (FTM2) Aluminum : 24 N / 25 mm High grade stainless steel : 25 N / 25 mm ABS : 22 N / 25 mm PP : 18 N / 25 mm HD-PE : 12 N / 25 mm LD-PE : 12 N / 25 mm

Additional Information

Example for order information

Event markers from 150 to 199 are required. The order is placed using the start number for the number range and the end number for the number range.

This results in the order designation **PCV-CM20-150-050-SET**. The number **50** in the order designation represents the number of event marker strips each measuring 1 m. The number **150** in the order designation represents the start number. NOTE: Event marker numbers from 1 ... 999 can be ordered as required. In this example, the delivery consists of 50 event marker strips, each measuring 1 m long. The event marker code tape is 1-meter long and can also be shortened if required. Please note that depending on the travel speed and the measuring rate of the read head, the event marker code tape must have a minimum length to be detected reliably.

Type Code

Structure of the type code

(Ordering information)																			
Ρ	С	V	-	С	М	2	0	-	(1)	(1)	(1)	-	(2)	(2)	(2)	-	S	E	Т
PCV				Sensor 1	уре														
PCV				Data Matrix positioning system (PCV)															
СМ				Code Ty	ре														
С				Data Matrix ECC200, Symbol size 12x12															
М				Event marker tape															
20				Width of the marker tape															
20				25 mm (2 row version)															
(1) (1) (1)			Start ma	rker nu	mber													
	999			Event marker start number															
(2) (2	2) (2)			Number															
	999			Number of event marker strips of 1 m each.															

Refer to "General Notes Relating to Pepperl+Fuchs Product Information"

2