



# Stopping Plugs, Metal, Hexagon Socket Head

## SP.MA.NPT1-1/2.BN.X.25.K05

- Stopping plug for unused cable entries
- Brass nickel-plated
- Thread NPT 1-1/2"
- Without head, installation by means of allen key
- Ex db, Ex eb and Ex tb certified
- Suitable for operation in Zone 1, Zone 2, Zone 21 and Zone 22
- Suitable for operation in Class I, Zone 1/2/22
- Suitable for operation in Class I, Division 2 when installed in accordance with NEC501.10(B)(2)
- Degree of protection IP66 / IP68, UL Type 4X
- Packaging unit: 5 pieces, without accessories










## **Dimensions**



#### Details see data table

Legend		
1	Stopping plug	
KS	Key size	
L	Total length	
TD	Thread size	
TL	Thread length	

#### **Technical Data**

Mechanical specifications	
Thread type	NPT ANSI ASME B1.20.1
Thread size (TD)	NPT 1-1/2"
Degree of protection	IP66 / IP68 , UL Type 4X
Material	

Technical Data	
E	
Finish	inherent color silver
Stopping plug	brass, nickel-plated
Mass	
Individual component	approx. 298 g
Packing unit	approx. 1.64 kg
Dimensions	
Thread length (TL)	25 mm
Total length (L)	25 mm
Key size (KS)	14 mm
Tightening torque	
Nut torque at enclosure (SW1)	15 Nm
Ambient conditions	
Ambient temperature	-60 130 °C (-76 266 °F)
Data for application in connection with haza	rdous areas
EU-type examination certificate	CESI 15 ATEX 029X
Marking	IDENTIFY TO BE TO
International approvals	
UL approval	
cULus	E305142 tested to UL 50E and UL 508A CSA C22.2, No. 14-13
IECEx approval	IECEx CES 15.0006X
UKCA approval	CML 22 UKEX 1267X
CCC approval	2021312313000343
Conformity	
Degree of protection	EN 60529
General information	
Delivery quantity	5
Scope of delivery	Stopping Plugs, Metal, Hexagon Socket Head Brief instructions (1 copy)
Supplementary information	EC-Type Examination Certificate, Statement of Conformity, Declaration of Conformity, Attestation of Conformity and instructions have to be observed where applicable. For information see www.pepperl-fuchs.com.