

RFID read/write device IPH-HH50

- Suitable for IPC data carrier
- Robust design, suitable for indoor and outdoor use
- Interchangeable module for IC-HH5x handheld

RFID read/write device 125 kHz (LF) for modular handheld



Technical Data

| General specifications | |
|-----------------------------|--|
| Operating frequency | 125 kHz |
| Electrical specifications | |
| Supply | via handheld reader |
| Directive conformity | |
| Radio equipment | |
| Directive 2014/53/EU | EN 300330 EN 62368-1 EN 62311 EN 301489-1 EN 55032 |
| RoHS | |
| Directive 2011/65/EU (RoHS) | IEC/EN 63000 |
| Standard conformity | |
| Degree of protection | EN 60529 |
| RFID | ISO/IEC 18000-2 |
| Approvals and certificates | |
| CE conformity | CE |
| FCC approval | This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation. Caution: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. |
| IC approval | This device complies with Industry Canada licence-exempt RSS standard(s) and with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference, including interference that may cause undesired operation of the device. Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes: (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement. |
| ISED approval | This device contains licence-exempt transmitter(s)/receiver(s) that comply with Innovation, Science and Economic Development Canada's licence-exempt RSS-310. Operation is subject to the following two conditions: (1) This device may not cause interference. (2) This device must accept any interference, including interference that may cause undesired operation of the device. |

Release date: 2023-10-17 Date of issue: 2023-10-17 Filename: 70119696_eng.pdf

Ambient conditions

| Technical Data | | |
|---------------------------|-----------------------|--|
| Ambient temperature | -20 50 °C (-4 122 °F) | |
| Storage temperature | -20 60 °C (-4 140 °F) | |
| Mechanical specifications | | |
| Housing length | 43.8 mm | |
| Housing width | 84.2 mm | |
| Housing height | 33.5 mm | |
| Degree of protection | IP54 | |
| Material | | |
| Housing | Plastic ABS/PC | |
| Mass | approx. 60 g | |