

Metal code bar

PXV000001M- AAMG30x100-001000-B


- High temperature resistance
- High mechanical stability
- Easily exchangeable
- Chemically highly resistant
- 2-colored Data Matrix codes

DataMatrix metal code bars for positioning safePXV and safePGV read heads

Function

Rugged Data Matrix metal code bars made of anodized aluminum for use on the ground in camera-based track guidance. Depending on the application, the code bars can be glued directly to the floor, or glued into special carrier profile rails. The code bars are available in modular lengths of 100, 200, and 500 mm.

Dimensions



Technical Data

| General specifications | |
|---------------------------|---|
| Total length | 1 m |
| Start position | 1000 m |
| Code bar segment | |
| Length | 100 mm |
| Width | 30 mm |
| Ambient conditions | |
| Operating temperature | -40 ... 80 °C (-40 ... 176 °F) |
| Installation temperature | 10 ... 40 °C (50 ... 104 °F) |
| Environmental resistance | UV radiation Humidity |
| Chemical resistance | Oils Grease Fuels Aliphatic solvents Weak acids |
| Mechanical specifications | |
| Material thickness | 1 mm |
| Material | Aluminum |
| Mounting type | adhesive |
| Mass | 83 g / m |
| Manufacturing tolerance | ± 4 mm/m |

Release date: 2022-05-04 Date of issue: 2022-05-04 Filename: 70144671-100025_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Mounting

Preparing the Base Surface

1. Use clean cleaning cloths (free from lint and plasticizers) to clean the surfaces.
2. Use cleaning agents appropriate for the level of surface contamination, for example n-Heptane, ethanol, or a 50:50 mixture of isopropanol and water.
3. Clean the surface until it is completely dry and free of dust, oil, oxides, release agents, and other contaminants.
4. Ensure that the surface is dry, clean, and stable.

Adhesive Strength

| Metal | Material with high-energy surfaces | Material with low-energy surfaces |
|------------|------------------------------------|-----------------------------------|
| 33 N/25 mm | 32 N/25 mm | 31 N/25 mm |

Material thickness: 1 mm code bar + 0.13 mm adhesive

Processing Instructions

During bonding, the pressure should be as high as possible, and the temperature should be at least +10 °C. The higher the pressure and temperature, the better the adhesive will penetrate the pores of the base surface. This allows higher adhesive strength values to be achieved. It takes approx. 72 hours for the adhesive to cure.

Type Code

Structure of the type code

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|---|-----|-----|-----|-----|-----|-----|---|---|---|---|---|-----|-----|-----|---|-----|-----|-----|---|-----|-----|-----|-----|-----|-----|---|---|
| P | X | V | (1) | (1) | (1) | (1) | (1) | (1) | M | - | A | A | M | (2) | (3) | (3) | x | (4) | (4) | (4) | - | (5) | (5) | (5) | (5) | (5) | (5) | - | B |
|---|---|---|-----|-----|-----|-----|-----|-----|---|---|---|---|---|-----|-----|-----|---|-----|-----|-----|---|-----|-----|-----|-----|-----|-----|---|---|

| PGV | Sensor Type |
|-----|--------------------------|
| PXV | Position Extended Vision |

| (1) (1) (1) (1) (1) (1) | Total length of the code bar |
|-------------------------|--|
| 1 ... 100,000 | The total length of the code bar is determined by the number of individual code bar segments. The code bars can be ordered in 1 m units. |

| M | Unit |
|---|------------------|
| M | Length in meters |

| AAM | Code Bar |
|-----|-------------------|
| A | Code bar |
| A | Absolute code bar |
| M | Metal code bar |

| (2) | Mounting Type |
|-----|---|
| G | Mounted by bonding with the adhesive applied to the back. Bonded directly on the floor or in special profile rails. |
| H | Mounted by screwing or riveting to the support material. |

| (3) (3) | Code Bar Width |
|---------|---|
| 30 | Width of the code bar in mm for mounting by bonding. |
| 50 | Width of the code bar in mm for mounting by screwing or riveting. |

| (4) (4) (4) | Code Bar Length |
|-------------|---|
| 100 | Length of the individual code bars in mm. |
| 200 | Length of the individual code bars in mm. |
| 500 | Length of the individual code bars in mm. |

| (5) (5) (5) (5) (5) (5) | Start position |
|-------------------------|---------------------------------------|
| 1 ... 99,999 | Start position of the code bars in m. |

| B | Version Information |
|---|---------------------|
| B | Version B |

Release date: 2022-05-04 Date of issue: 2022-05-04 Filename: 70144671-100025_eng.pdf