




Inductive sensor

NAN20-30GM35-E2-IO-V1

- Parameterization and diagnosis via IO-Link
- Measuring range 0 ... 20 mm
- Non-flush mountable
- Flexible use with versatile mounting opportunities
- Extensive maintenance functions for condition monitoring
- Determining of speed and acceleration of the damping element


Inductive distance sensor with IO-Link interface



Function

The inductive distance sensors with IO-Link offer a wide range of functions. In addition to continuous distance measurement, 2 switch points or windows can be parameterized in different operating modes. The additional determination of the speed and acceleration of the damping element also allows monitoring options for special braking and acceleration processes or for opening and closing processes. Adjustable filters allow the measurement speed and accuracy to be adapted to the application requirements. All this comprehensive additional data and parameterizable limit values enable perfect condition monitoring of the application/machine, for example for temperature, operating times, counters and also symptoms of wear. Process and service data can be transferred via IO-Link, enabling easy integration into Industry 4.0 applications.

Dimensions



Technical Data

General specifications			
Switching function		Normally open/closed (NO/NC) programmable	
Output type		PNP	
Installation		non-flush	
Output polarity		DC	
Actuating element		mild steel, e. g. 1.0037, SR235JR (formerly St37-2) 60 mm x 60 mm x 1 mm	
Measuring range		0 ... 20 mm	
Output type		3-wire	
Nominal ratings			
Operating voltage	U _B	10 ... 30 V (SIO mode) 18 ... 30 V (IO-Link)	
Switching frequency	f	SIO mode: 400 Hz (high speed filter)	
Hysteresis	H	1 ... 20 % (factory setting: 5 %)	
Reverse polarity protection		reverse polarity protected	

Technical Data

Short-circuit protection		pulsing
Voltage drop	U_d	$\leq 1 \text{ V}$
Linearity error		$\pm 3 \text{ %}$ of full-scale value
Temperature drift		$\pm 10 \text{ %}$ of full-scale value
Repeat accuracy		$\pm 1 \text{ %}$ of full-scale value
Speed measuring range		1 ... 3000 mm/s
Speed measurement accuracy		$\pm 20 \text{ %}$ of the full-scale value
Speed measurement repeat accuracy		$\pm 5 \text{ %}$ of the full-scale value
Operating current	I_L	0 ... 100 mA
Off-state current	I_r	max. 30 μA
No-load supply current	I_0	17 mA
Time delay before availability	t_v	max. 100 ms
Switching state indicator		Multihole-LED, yellow permanently on: switching output active permanently off: switching output inactive fast flashing (10 Hz): fault state
Safety-relevant product characteristics		
MTTF _d		1410 a
Mission Time (T_M)		20 a
Diagnostic Coverage (DC)		0 %
Interface		
Interface type		IO-Link (via C/Q = pin 4)
IO-Link revision		1.1
Device profile		Identification and Diagnosis - I&D Smart Sensor - SSP 0 Smart Sensor - SSP 4.1.1
Process data		Input: 32 Bit - measurement value 16 Bit - scaling 8 Bit - Diagnosis signals 3 Bit - switching signals 2 Bit
Vendor ID		1 (0x0001)
Device ID		2098952 (0x200708)
Transfer rate		COM2 (38.4 kBit/s)
Min. cycle time		3.2 ms
SIO mode support		yes
Compatible master port type		Class A , Class B
Conformity		
PWIS conformity		VDMA 24364-A1/B2/C1/T100°C-W
Compliance with standards and directives		
Standard conformity		
Standards		EN IEC 60947-5-2 EN IEC 60947-5-7
Approvals and certificates		
Protection class		II
Rated insulation voltage	U_i	30 V
Rated impulse withstand voltage	U_{imp}	500 V
UL approval		cULus Listed Load Type: General Purpose Circuitry: Class 2 Power Source Enclosure Type Rating: Type 1 Supply/Switching Voltage: 30 V DC Output Switching Current: 100 mA
CCC approval		CCC approval / marking not required for products rated $\leq 36 \text{ V}$
Ambient conditions		
Ambient temperature		-25 ... 70 °C (-13 ... 158 °F)
Storage temperature		-40 ... 85 °C (-40 ... 185 °F)
Mechanical specifications		
Connection type		Connector plug

Release date: 2026-02-27 Date of issue: 2026-02-27 Filename: 70145056-0055_eng.pdf


Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.comUSA: +1 330 486 0001
fa-info@us.pepperl-fuchs.comGermany: +49 621 776 1111
fa-info@de.pepperl-fuchs.comSingapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com
 **PEPPERL+FUCHS**


Technical Data

Housing material	brass , white bronze coated	
Sensing face		PBT , green
Degree of protection	IP65/IP67/IP68	
Connector		
Threading	M12 x 1	
Number of pins		3
Mass	104 g	
Dimensions		
Length	51 mm	
Diameter	30 mm	
Mounting	with nuts, M30	
Tightening torque		≤ 30 Nm
General information		
Scope of delivery		2 self locking nuts in scope of delivery

Connection Assignment



Connection Assignment



Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Release date: 2026-02-27 Date of issue: 2026-02-27 Filename: 70145056-0055_eng.pdf

Characteristic Curve

