

Programming adapter P-PROG-R4-USB-Set



■ Programming adapter set

Programming adapter for vision sensors and positioning systems with an RS-485 programming interface



Function

The programming adapter enables communication between the device and a PC via the RS-485 interface for use with the Vision Configurator. To connect the device, it is connected to the programming adapter via the screw terminals or the adapter cable.

Technical Data

Indicators/operating means		
Operation indicator		LED red
Data flow indicator		LED yellow and LED green
Electrical specifications		
Operating voltage	U _B	via USB
Interface 1		
Connection of		PC
Interface type		USB
Interface 2		
Connection of		Read head
Interface type		RS-422 / RS-485
Transfer rate		up to 921.6 kBit/s
General information		
Scope of delivery	USB connection cable Adapter cable, M12, 8-pin, shielded, PVC cable, 9-pin D-Sub female connector, DC 5.5 x 2.1 mm barrel jack Adapter cable, M12, 8-pin, M12, 5-pin, shielded, PVC cable USB to RS 485 interface converter	

Release date: 2026-08-14 Date of issue: 2026-08-14 Filename: 70211445_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**