


# Retroreflective sensor

## OBS 10M-30GM90-U-V124



- Rugged housings withstand harsh environments
- Connector
- Polarization filter allows detection of shiny objects
- Tempered glass lens cover and Viton seals resist harsh environments
- Sensing range 10 m

30 mm Diameter Series



### Technical Data

#### General specifications

Detection range	10 meters
Light source	Visible red LED 680 nm
Polarization filter	yes
Ambient light limit	≤ 100000 Lux
Hysteresis	H ≤ 15%

#### Indicators/operating means

Function indicator	dark on
--------------------	---------

#### Electrical specifications

Operating voltage	$U_B$	20 ... 132 V AC, 50/60 Hz, 15 ... 30 V DC
No-load supply current	$I_0$	≤ 100 mA
Operating current	$I_B$	300 mA max
Protection class		IP68

#### Output

Switching type		light/dark on
Signal output		Bi-directional thyristor (AC) or NPN (DC)
Voltage drop	$U_d$	≤ 4 V (DC operation)
Switching frequency	f	50 Hz
Response time		≤ 10 ms (AC), ≤ 2 ms (DC)

#### Standard conformity

Standards	EN 60947-5-2
-----------	--------------

#### Approvals and certificates

Approvals	CE
-----------	----

#### Ambient conditions

Ambient temperature	-40 ... 55 °C (-40 ... 131 °F)
Storage temperature	-40 ... 55 °C (-40 ... 131 °F)

#### Mechanical specifications

Degree of protection	IP68
Connection	178 mm fixed cable with V124 quick disconnect
Material	
Housing	Stainless steel 1.4305 / AISI 303
Optical face	Tempered glass
Mass	147 g

Release date: 2020-09-15 Date of issue: 2020-09-15 Filename: 903398\_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group  
www.pepperl-fuchs.com

USA: +1 330 486 0001  
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111  
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091  
fa-info@sg.pepperl-fuchs.com

 PEPPERL+FUCHS