



KVM Workstation KM921 Series

- 21.5 inch Full HD display with optional touch screen
- Widescreen 16:9 aspect ratio
- Ruggedized housing
- Various keyboard/mouse options
- Connects to host PC via internal KVM extender
- Class I, Div. 2 / ATEX Zone 2 approved

21.5 inch (54.6 cm) industrial KVM monitor



Function

VisuNet IND KM921 rugged industrialized housing was made to extend the control room into the toughest process conditions. The KVM extender option allows the display and the host PC to be up to 400 m (1300 ft) apart and is certified for installation in Class I/Div 2 and ATEX Zone 2 locations.



Designed for manufacturing environments where dust, bacteria, water, and other undesirable materials might accumulate, the enclosure construction and surfaces provide wash down solutions proper drainage to prevent standing water and easily mounts utilizing the industry standard 100 mm VESA.

This 21.5" monitor features an optional touch screen, keyboard with various mouse options, and choice of one of three KVM types.



Connection

SP7 / SS7

CAT5 Terminals	Description
1.1	BI_DA + WH/GN
1.2	BI_DA - GN
1.3	BI_DB + WH/OR
1.4	BI_DC + BU
1.5	BI_DC - WH/BU
1.6	BI_DB - OR
1.7	BI_DD + WH/BN
1.8	BI_DD - BN



SP5 / SS5



Release date: 2023-05-23 Date of issue: 2023-05-23 Filename: t181823_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com


USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com

Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Dimensions



Release date: 2023-05-23 Date of issue: 2023-05-23 Filename: t181823_eng.pdf

Technical Data

General specifications	
Distance	Transmitter "K4": 120 m (400 ft) Transmitter "K5": 200 m (650 ft), 62.5 μ multimode; 400 m (1300 ft), 50.0 μ multimode
Supply	
Connection	Monitor: power, CAT5, fiber (LC)
Power consumption	Main unit: 50 ... 60 Hz; 20-30 VDC Transmitter "K4": 5 VDC @ 10 W, max Transmitter "K5": 5 VDC @ 10 W, max
Indicators/operating means	

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Technical Data

Indicators	Transmitter "K4": video check LED; front panel - power Transmitter "K5": video check LED; front panel - power
Display	
Screen diagonal	21.5 inch (546 mm)
Response time	25 ms (standard brightness) 5 ms (high brightness)
Resolution	1920 x 1080 Full HD
Color depth	24 bit (16.7 M) color
Contrast	5000:1 (standard brightness) 900:1 (high brightness)
Brightness	300 cd/m ² (nits) - standard brightness 1200 cd/m ² (nits) - high brightness
Reading angle	89° in all directions (standard brightness) 170° H; 160° V (high brightness)
Life span	back lamp life: 50,000 hrs typical half life
Input devices	Transmitter "K4": 29-pin DVI-D; 2 x USB Type B (keyboard, mouse/touchscreen); 1 x RS232 (touchscreen); 1 x RJ45 (CAT5e/6) Transmitter "K5": 29-pin DVI-D; 1 x USB Type B (keyboard, mouse/touchscreen); 1 x RS232 (touchscreen); fiber optic (multimode) LC connectors
Touchscreen	5-wire resistive 5-wire hardened resistive
Keyboard	touchpad , optical trackball (50 mm) , joystick
Serial data	
Baud rate	19.2 KBd max
Flow control	RTS, CTS, DTR, DSR
Directive conformity	
Electromagnetic compatibility	
Directive 89/336/EEC	EN55022A, EN61000-6-2, EN61000-3-2, EN61000-3-3
Ambient conditions	
Operating temperature	-20 ... 45 °C (-4 ... 113 °F)
Storage temperature	-20 ... 60 °C (-4 ... 140 °F)
Relative humidity	0 ... 90% (noncondensing)
Shock resistance	30g, 11 ms, all axis
Vibration resistance	5 ... 100 Hz 1G, 12 m/s ²
Mechanical specifications	
Degree of protection	Type 4X (stainless steel) Type 4 (painted steel) IP66
Material	Main enclosure: painted black steel or 316L stainless steel Main enclosure (rear cover): 6062 anodized aluminum, marine grade
Installation	100 mm (3.9 inch) VESA mount
Mass	Main unit: 15.9 kg (35 lb) without keyboard; 21.3 kg (47 lb) with keyboard Transmitter "K4": 0.3 kg (0.7 lbs) Transmitter "K5": 0.3 kg (0.7 lbs)
Dimensions	Main enclosure: 636 x 406 x 86 mm (25.0 x 16.0 x 3.4 inch), junction box adds 43 mm (1.7 inch) to depth Keyboard enclosure: 559 x 254 x 51 mm (22.0 x 10.0 x 2.0 inch) Transmitter "K4": 104 x 135 x 36 mm (4.1 x 5.3 x 1.4 inch) Transmitter "K5": 104 x 135 x 36 mm (4.1 x 5.3 x 1.4 inch)
Data for application in connection with hazardous areas	
EU-type examination certificate	
Marking	Ⓔ II 3G Ex ic nA IIC T4 Gc
International approvals	
ETL approval	Class I, Div. 2 Groups A, B, C, D; T4

Accessories

	VESA CABLE FEEDTHROUGH	Slimline adapter plate
---	-------------------------------	------------------------

Release date: 2023-05-23 Date of issue: 2023-05-23 Filename: t181823_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0002
pa-info@us.pepperl-fuchs.com


Germany: +49 621 776 2222
pa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
pa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Type Code

K M 9 2 1 A - D 2 - K 5 A C - S S 7 N K 0 L 0 - S 0 - N



Options
N No options

Special accessories
S0 No special accessories

Keyboard layout
L0 No keyboard, no layout
US Keyboard, layout U.S.

Keyboard/mouse version
K0 No keyboard, no mouse
K4 Foil keyboard & capacitive touchpad mouse
K6 Foil keyboard & joystick
K8 Foil keyboard & 50 mm optical trackball mouse
K9 Foil keyboard & resistive touchpad mouse

Keyboard housing
N No keyboard, no mouse
C Hinge mounted

Housing version
SP5 IND housing, black painted steel, rear junction box with IP67 connectors - "GP" Protection only
SS5 IND stainless steel (316L) housing, rear junction box with IP67 connectors - "GP" Protection only
SP7 IND housing, black painted steel, rear junction box with cable glands
SS7 IND stainless steel (316L) housing, rear junction box with cable glands

Power supply
DC 24 V DC

Board specifications
K4 KVM for DVI-D video included, 2x USB interface, 1x RS232, CATx cable transmission
K5 KVM for DVI-D video included, 2x USB interface, 1x RS232, fiber-optic transmission (multi-mode), 2x LC connectors

Protection
V3 Class I, Div. 2 Groups A, B, C, D / ATEX Zone 2
GP Industrial, Non-EX
D2 Class I, Div. 2 Groups A, B, C, D

Screen type
A Antiglare glass front, non-touch
R Touch screen, resistive, 5-wire, hardened glass
T Touch screen, resistive, 5-wire
U High-bright display, with touch screen, 5-wire resistive
F High-bright display, non-touch, antiglare
K High-bright display, with touch screen, 5-wire hardened resistive

KM921 KVM monitor, 21.5" (54.6 cm), Full HD (1920 x 1080), internal KVM extender

Release date: 2023-05-23 Date of issue: 2023-05-23 Filename: 1181823_eng.pdf