



# **Direct Monitor**

## VisuNet GMP DM219

- Direct Monitor
- 19 inch monitor (48.3 cm)
- Direct data transfer via VGA or DVI interface
- Adapted for distances up to 5 m




#### **Function**

Visunet GMP devices are operator workstations for use in GMP conditions and come with a manufacturer's declaration of conformity to this effect. Typical application locations are the pharmaceutical and food industries as well as the production of cosmetics, flavour and nutrition.

The operator workstations are available as Direct Monitors, KVM Monitors, Remote Monitors and as Panel PCs. The Direct Monitors can be connected directly to the Host PC via the VGA or DVI port.


Direct Monitors support the cost-effective visualization of processes in close proximity to the Host PC.

### Connection



- Α Phoenix DFK-MSTB 2,5/4-GF-5,08
- В Ground connection (M4)
- С VGA interface
- **DVI** interface D

#### **Dimensions**



_			-	_		
Te	abı	aia	$\sim$	П	a +	
	-				5 I I	

General specifications	
Type	Direct Monitor
Supply	
Power supply	20 30 V DC ; 90 240 V AC , 50 60 Hz
Power consumption	40 W
Indicators/operating means	
Display	
Туре	TFT, LCD, High Color (19 bit)
Screen diagonal	48.3 cm (19 inch)
Resolution	1280 x 1024 Pixel
Color depth	16.7 Mio.
Brightness	300 cd/m <sup>2</sup> (nit)
Input devices	Analog resistive touchscreen (optional) , Keyboard with integrated mouse functionality: optical trackball/touchpad/joystick versions available
Interface	
Interface type	VGA or DVI
Ambient conditions	
Ambient temperature	0 50 °C (32 122 °F)
Storage temperature	-10 60 °C (14 140 °F)
Relative humidity	max. 85 % non-condensing
Mechanical specifications	
Degree of protection	IP65
Material	
Surface	stainless steel 1.4301 / AISI 304
Surface quality	$R_a$ 0.8 $\mu m$
Mounting type	slim line housing several mounting types (pedestal, wall bracket, wall arm - each turnable or fix) available
Mass	approx. 12 kg
Dimensions	568 mm x 450 mm x 73 mm

Release date: 2021-11-09 Date of issue: 2021-11-09 Filename: t44981\_eng.pdf

rersion.

Гуре	уре	Ē	Board specification	hply	Housing frontplate ve	Keyboard housing	Keyboard Mouse ver	Keyboard Layout	ries	
Monitor Type	Screen Type	Protection	Board sp	Power supply	Housing	Keyboar	Keyboar	Keyboar	Accessories	Options
Monitor										
DM21 Video Monitor 19" 9										
Э	Screen Type									
	Α									
	R		Touch screen, resistive							
	Е			ass, e	ss, etched					
		Protection  GP Industrial, non-Ex version								
	Board Specification									
	V1 VGA and DVI									
	Power supply									
	D 24 VDC									
	Housing frontplate version									
SL2 Slim-Line stainless steel h					Slin	n-Line	stainle	ess ste	pel housing	
					N	Kev	board	housi	na	
Keyboard housing  N No keyboard & mo									mouse housing	
									use housing, stainless steel	
	C Keyboard & mouse housing, tiltable 90° -180°, stainless steel  Keyboard / Mouse version									
							Key K0			
,				K4		-	ard & touchpad mouse built in			
				K6	Foil	keybo	ard & joystick mouse built in			
				K8			ard & optical trackball mouse built in			
Keyboard Layou							Keyl L0			
					DE		board layout German			
							board layout US-international			
							board layout French			
									board layout Danish	
	ES Keyboard layout Spanish Special accessories									
	S0 No special accessories									
	Options									
N No options										
Y Non-standard customized version										